




### > STRENGTHS:

- Sealed combustion: operates in an airtight chamber without using room air - certified safe even for bedroom installation
- Fully airtight and isolated from the environment: does not consume indoor oxygen
- Thermal power up to 9.7 kW
- Efficiency up to 95%
- Large-capacity pellet hopper (15 or 22 kg), requiring refilling every 3 days (model-dependent)
- Suitable for heating rooms up to 82 m<sup>2</sup>
- Uses external air for combustion via intake duct
- Long lifespan thanks to its cast iron burner
- Available in two colors: bordeaux and black

### > INTEGRATED DIGITAL CONTROL PANEL

- Set your desired room temperature
- Automatic modulation of pellet consumption based on the selected or reached temperature
- Alerts in case of system faults or blockages
- Weekly programmable thermostat (chronothermostat)



**NEW AESTHETICS  
WITH ROUNDED  
EDGES**

### CONTROL PANEL

This compact control panel contains all the functions needed to manage the appliance, in particular:

- view information during operation
- view and modify operating parameters
- view the operating status and various settings
- switch on and off, including setting the appliance to chronothermostat mode

| MODEL                                           |                   | 7                               | 9               | 11              |
|-------------------------------------------------|-------------------|---------------------------------|-----------------|-----------------|
| ErP Class                                       |                   |                                 |                 |                 |
| Fuel type                                       |                   | Wood pellet - EN ISO 17225-2_A1 |                 |                 |
| Heat output *                                   | kW                | 5.9 - 2.2                       | 7.9 - 3.0       | 9.4 - 3.0       |
| Thermal efficiency *                            | %                 | 87 - 90.4                       | 90.2 - 94.3     | 88.6 - 94.3     |
| CO emissions (13% O <sub>2</sub> ) *            | mg/m <sup>3</sup> | 246 - 188                       | 33 - 96         | 46 - 96         |
| Pellet consumption **                           | kg/h              | 1.41 - 0.5                      | 1.81 - 0.67     | 2.2 - 0.67      |
| Pellet storage capacity                         | kg                | 15                              | 22              | 22              |
| Maximum flue gas temperature                    | °C                | 182.6                           | 145.8           | 171.2           |
| Flue gas outlet                                 | mm                | Ø 80                            | Ø 80            | Ø 80            |
| Minimum chimney draft required                  | Pa                | 12                              | 12              | 12              |
| Combustion air inlet                            | mm                | Ø 50                            | Ø 50            | Ø 50            |
| Electrical supply                               | V/Hz              | 230 / 50                        | 230 / 50        | 230 / 50        |
| Power consumption (ignition / normal operation) | W                 | 370 / 52                        | 370 / 87        | 370 / 89        |
| Weight                                          | kg                | 49                              | 79              | 79              |
| Dimensions (height / width / depth)             | mm                | 890 / 430 / 503                 | 953 / 460 / 540 | 953 / 460 / 540 |
| Heatable volume ***                             | m <sup>3</sup>    | 168 - 118                       | 225 - 158       | 268 - 188       |
| CODE                                            | BORDEAUX          | OSS023XA                        | OSS043XA        | OSS063XA        |
|                                                 | BLACK             | OSS029XA                        | OSS049XA        | OSS069XA        |
| WI-FI ACCESSORY                                 |                   | 083000X0                        |                 |                 |

(\*) at Nominal and Minimum power

(\*\*) Fuel consumption may vary depending on the type of pellet used

(\*\*\*) Depending on the insulation status of the home and calculated on 35 W/m<sup>3</sup>