

# SweetWater PRO

## Dedurizatoare



Gama SweetWater PRO oferă dedurizatoare fiabile și compacte, concepute pentru a asigura o performanță ridicată în tratarea apei, atât pentru uz rezidențial, cât și pentru aplicații tehnologice.

### Performanță și eficiență

- Conținut de 20 sau 30 litri de rășini cationice cu capacitate mare de schimb ionic
- Eficiență maximă în reducerea durtății apei
- Consum optimizat de apă, sare și energie electrică
- Sistem integrat de amestec pentru reglarea durtății reziduale

### Control inteligent și regenerare automată

- Regenerare combinată în funcție de timp și volum
- Vană automată de comandă electromecanică
- Gestiune electronică avansată pentru control complet al fazelor de regenerare
- Afișare constantă a volumului de apă tratată

### Instalare și utilizare

- By-pass încorporat în vana de comandă
- Livrat cu toate accesoriile necesare pentru o instalare corectă
- Programare simplă și rapidă
- Potrivit pentru tratarea apei menajere și a apei cu destinație tehnologică

### Modele disponibile

- **SweetWater PRO 20**
- **SweetWater PRO 30**



| Caracteristică     | u.m.  | SweetWater PRO 20 | SweetWater PRO 30 |
|--------------------|-------|-------------------|-------------------|
| Cantitate rășină   | litri | 20                | 30                |
| Capacitate sare    | kg    | 41                | 58                |
| Dimensiuni (DxWxH) | mm    | 485x370x1108      | 485x370x1335      |
| Greutate transport | kg    | 39                | 45                |

| Capacitate de dedurizare – Dozaj sare |      |                   |                   |
|---------------------------------------|------|-------------------|-------------------|
| Caracteristică                        | u.m. | SweetWater PRO 20 | SweetWater PRO 30 |
| 48 g/L                                | g    | 689               | 1071              |
| 96 g/L                                | g    | 1087              | 1629              |
| 160 g/L                               | g    | 1450              | 1993              |

# SweetWater PRO

## Water Softeners



The SweetWater PRO range includes reliable and compact water softeners designed to deliver high performance in water treatment applications, suitable for both residential and technological use.

### Performance and Efficiency

- 20 or 30 liters of high-capacity cation exchange resin
- Maximum efficiency in hardness removal
- Optimized consumption of water, salt, and electrical energy
- Integrated blending system for residual hardness adjustment

### Smart Control and Automatic Regeneration

- Combined regeneration based on time and volume
- Electromechanical automatic control valve
- Advanced electronic management ensuring full control of regeneration phases
- Continuous display of treated water volume

### Installation and Application

- Built-in bypass integrated into the control valve
- Supplied with all accessories required for proper installation
- Easy valve programming and setup
- Suitable for the treatment of domestic and process water

### Modele disponibile

- **SweetWater PRO 20**
- **SweetWater PRO 30**



| Feature            | m.u.   | SweetWater PRO 20 | SweetWater PRO 30 |
|--------------------|--------|-------------------|-------------------|
| Resin quantity     | liters | 20                | 30                |
| Salt capacity      | kg     | 41                | 58                |
| Dimensions (LxWxH) | mm     | 485x370x1108      | 485x370x1335      |
| Transport weight   | kg     | 39                | 45                |

| Softening capacity – Salt dosage |      |                   |                   |
|----------------------------------|------|-------------------|-------------------|
| Feature                          | m.u. | SweetWater PRO 20 | SweetWater PRO 30 |
| 48 g/L                           | g    | 689               | 1071              |
| 96 g/L                           | g    | 1087              | 1629              |
| 160 g/L                          | g    | 1450              | 1993              |