

EG-Baumusterprüfbescheinigung**EC type examination certificate****CE-0085BQ0065**Produkt-Identnummer
product identification no.

Anwendungsbereich <i>field of application</i>	EG-Gasgeräte-richtlinie (90/396/EEG) <i>EC Gas Appliances Directive (90/396/EEC)</i>
Zertifikatinhaber <i>owner of certificate</i>	Ferrol S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Vertreiber <i>distributor</i>	Ferrol S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Produktart <i>product category</i>	Boilers: Boiler with atmospheric burner (3121)
Produktbezeichnung <i>product description</i>	Boiler with atmospheric burner
Modell <i>model</i>	PEGASUS...LN 2S
Bestimmungsländer <i>countries of destination</i>	AT, BE, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, SE, SI, SK
Prüfberichte <i>test reports</i>	supplement test: K 370 2009 E1 from 24.04.2009 (TRG)
Prüfgrundlagen <i>basis of type examination</i>	EU/90/396/EEG (29.06.1990) DIN EN 297 (01.07.1998) DIN EN 656 (01.01.2000)
Aktenzeichen <i>file number</i>	09-0409-GEA

30.06.2009 Rie A-1/2

Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle
date, issued by, sheet, head of certification body

DVGW CERT GmbH - von der Deutschen Bundesregierung benannte und von der Europäischen Kommission offiziell registrierte Stelle für die Konformitätsbewertung von Gasgeräten

DVGW CERT GmbH - notified by the government of the Federal Republic of Germany and officially registered by the European Commission for conformity assessment of gas appliances

ZLS

ZLS-ZE-527/07

DVGW CERT GmbH
Josef-Wirmer-Straße 1-3
53123 BonnTelefon: +49 228 91 88-888
Telefax: +49 228 91 88-993
eMail: info@dv-gw-cert.com

Elektrische Daten: 230 V AC, 50 Hz
electrical data

Gerätekatategorien <i>appliance categories</i>	Versorgungsdrücke <i>supply pressures</i>	Bestimmungsländer <i>countries of destination</i>	Bemerkungen <i>remarks</i>
I2E	20 mbar	PL	
I2E+	20/25 mbar	BE	
I3+	28-30/37 mbar	BE	
I3B/P	30 mbar	CY, HU, MT	
II2E+3+	20/25, 28-30/37 mbar	FR	
II2E3B/P	20, 50 mbar	LU	
II2ELL3B/P	20, 50 mbar	DE	
II2H3+	20, 28-30/37 mbar	CH, ES, GB, GR, IE, IS, IT, NO, PT	
II2H3B/P	20, 30 mbar	CZ, DK, EE, FI, LT, LV, SE, SI, SK	
II2H3B/P	20, 50 mbar	AT	
II2L3B/P	25, 30 mbar	NL	
II2L3B/P	25, 50 mbar	NL	

Installationsarten <i>installation codes</i>	Bestimmungsländer <i>countries of destination</i>	Bemerkungen <i>remarks</i>
B11	AT, BE, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, SE, SI, SK	
B11BS	AT, BE, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MT, NL, NO, PL, PT, SE, SI, SK	

Type <i>type</i>	Technische Daten <i>technical data</i>	Bemerkungen <i>remarks</i>
PEGASUS 119 LN 2S	nominal heat output: 119 kW heat input (Hi): 74,8...131,0 kW	
PEGASUS 136 LN 2S	nominal heat output: 136 kW heat input (Hi): 74,8...149,0 kW	
PEGASUS 153 LN 2S	nominal heat output: 153 kW heat input (Hi): 93,6...168,0 kW	
PEGASUS 170 LN 2S	nominal heat output: 170 kW heat input (Hi): 93,6...187,0 kW	
PEGASUS 187 LN 2S	nominal heat output: 187 kW heat input (Hi): 112,0...206,0 kW	
PEGASUS 221 LN 2S	nominal heat output: 221 kW heat input (Hi): 131,0...243,0 kW	
PEGASUS 255 LN 2S	nominal heat output: 255 kW heat input (Hi): 149,0...280,0 kW	
PEGASUS 289 LN 2S	nominal heat output: 289 kW heat input (Hi): 168,0...317,0 kW	