

EC type examination certificate

EG-Baumusterprüfbescheinigung

CE-0085BM0383

Product Identification No.
Produkt-Identnummer

Field of Application <i>Anwendungsbereich</i>	EC Gas Appliances Directive (2009/142/EC) EG-Gasgeräte-Richtlinie (2009/142/EG)
Owner of Certificate <i>Zertifikatinhaber</i>	Ferrol S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Distributor <i>Vertreiber</i>	Ferrol S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Product Category <i>Produktart</i>	Boilers: Boiler with atmospheric burner (3121)
Product Description <i>Produktbezeichnung</i>	Boiler with atmospheric burner
Model <i>Modell</i>	Pegasus D...; Pegasus...LN2S; Pegasus...2S
Countries of Destination <i>Bestimmungsländer</i>	AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, NL, NO, PL, PT, SE
Test Reports <i>Prüfberichte</i>	supplement test: K 3672012 E3 from 01.03.2012 (TRG) supplement test: K 3672012 E4 from 01.03.2012 (TRG) supplement test: K 3672011 E2 from 20.07.2011 (TRG)
Test Basis <i>Prüfgrundlagen</i>	EU/2009/142/EG (30.11.2009) DIN EN 297 (01.10.2005) DIN EN 483 (01.06.2000) DIN EN 656 (01.01.2000) DIN EN 625 (01.10.1995)
File Number <i>Aktenzeichen</i>	12-0206-GER

70228-04-A-0E

06.07.2017 Rie A-1/2

Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DVGW CERT GmbH is an accredited body by DAkkS according to DIN EN ISO/IEC 17065:2013 and notified by the government of the Federal Republic of Germany for certification of gas appliances under EC Directive

DVGW CERT GmbH ist von der DAkkS nach DIN EN ISO/IEC 17065:2013 akkreditierte und von der Deutschen Bundesregierung benannte Stelle für die Zertifizierung von Gasgeräten gemäß EG-Richtlinie 2009/142/EG.



Deutsche
Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle

Josef-Wirmer-Str. 1-3
53123 Bonn

Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993

www.dvgw-cert.com
info@dvgw-cert.com

Elektrical Data
Elektrische Daten

230 V AC, 50 Hz

Appliance Categories <i>Gerätekategorien</i>	Supply Pressures <i>Versorgungsdrücke</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
I2E+	20/25 mbar	BE	
I3+	28-30/37 mbar	BE	
I12E LwLs3B/P	20,20,13, 36 mbar	PL	
I12E+3+	20/25, 28-30/37 mbar	FR	
I12E3B/P	20, 50 mbar	DE, LU	
I12H3+	20, 28-30/37 mbar	CH, ES, GB, GR, IE, IS, IT, NO, PT	
I12H3B/P	20, 30 mbar	DK, FI, SE	
I12H3B/P	20, 50 mbar	AT	
I12HS3B/P	25, 30 mbar	HU	
I12L3B/P	25, 30 mbar	NL	
I12L3B/P	25, 50 mbar	NL	

Installation Codes <i>Installationsarten</i>	Countries of Destination <i>Bestimmungsländer</i>	Remarks <i>Bemerkungen</i>
B11	AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IS, IT, LU, NL, NO, PT, SE	
B11BS	AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IS, IT, LU, NL, NO, PT, SE	

Type <i>Typ</i>	Technical Data <i>Technische Daten</i>	Remarks <i>Bemerkungen</i>
Pegasus D23	nominal heat output: 8,8...23,0 kW heat input (Hi): 10,1...25,3 kW	
Pegasus D32	nominal heat output: 13,0...32,0 kW heat input (Hi): 14,9...34,9 kW	
Pegasus D45	nominal heat output: 17,2...45,0 kW heat input (Hi): 19,7...49,5 kW	
Pegasus D56	nominal heat output: 21,6...56,0 kW heat input (Hi): 24,5...61,6 kW	
Pegasus 67 LN2S; Pegasus 67 2S	nominal heat output: 33,5...67,0 kW heat input (Hi): 36,6...73,3 kW	
Pegasus 77 LN2S; Pegasus 77 2S	nominal heat output: 44,0...77,0 kW heat input (Hi): 48,1...84,2 kW	
Pegasus 87 LN2S; Pegasus 87 2S	nominal heat output: 44,0...87,0 kW heat input (Hi): 48,1...95,2 kW	
Pegasus 97 LN2S; Pegasus 97 2S	nominal heat output: 54,0...97,0 kW heat input (Hi): 59,1...106,0 kW	
Pegasus 107 LN2S; Pegasus 107 2S	nominal heat output: 54,0...107,0 kW heat input (Hi): 59,1...117,0 kW	
Pegasus D20	nominal heat output: 9,1...20 kW nominal heat input (Hi): 10,1...21,5 kW	
Pegasus D30; Pegasus D30 K130/KI130/K100/KI100	nominal heat output: 13,5...30,2 kW nominal heat input (Hi): 14,9...32,2 kW	
Pegasus D40; Pegasus D40 K130/KI130/K100/KI100	nominal heat output: 17,7...40,1 kW nominal heat input (Hi): 19,7...42,9 kW	
Pegasus D50	nominal heat output: 22,0...50,2 kW nominal heat input (Hi): 24,5...53,5 kW	

Type Variation <i>Ausführungsvariante</i>	Explanations <i>Erläuterungen</i>
...LN...	with LOW-Nox-burner
Pegasus D... K130	with 130 l drinking water storage
Pegasus D... KI130	with 130 l INOX drinking water storage
Pegasus D... K100	with 100 l drinking water storage
Pegasus D... KI100	with 100 l INOX drinking water storage

