



Certificate number: 2202713 (1)

Issued 10/02/2022

Expires 10/02/2027

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Ferrolti Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:

Ferrolti Ltd
The Granary
Borough Hill Farm
Catton Road
Walton on Trent
Swadlincote
Derbyshire
DE12 8LL



Product Certificate

Appendix to Certificate number: 2202713

The following products belong to this certificate

PRODUCT DESCRIPTION Range of wall hung, gas-fired combination boilers providing domestic hot water via a plate heat exchanger and pressure relief valve set at 3.0 bar. The supply to the secondary water supply is controlled via a spherical valve. ATS3 – Without Production Surveillance.
MODEL(S) Bluehelix HITECH RRT 24C; Bluehelix HITECH RRT 28C; Bluehelix HITECH RRT 34C.
SIZE: ½" BSP(M) secondary. ¾" BSP(M) primary.
SCOPE: Manufacturer recommended maximum working pressure: Secondary 9 Bar & maximum operating temperature 65°C, Primary 2.5 Bar. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 65°C. Wall Mounted.
MARKING Ferroli on control panel. Ferroli, address, model no, serial no, pressure rating and other technical information on data label.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES No supply pipe or secondary circuit shall be permanently connected to a closed circuit for filling a heating system unless it incorporates an appropriate backflow prevention device.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements. A filling loop is not supplied as part of this approval.

Extra Notes