



Certificate number: 2309816 (2)

Issued 27/09/2023

Expires 27/09/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Ferrol S.p.A.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Ferrol S.p.A
Via Ritonda 78A
37047 S.Bonifacio (VR)
Italy



KUKreg4

Product Certificate

Appendix to Certificate number: 2309816

The following products belong to this certificate

PRODUCT DESCRIPTION Range of electrically heated unvented water heaters having an enamel lining, with or without solar coil and magnesium anode. Fitted with a temperature and pressure relief valve set at 7 bar and 90°C ATS3 – Without Production Surveillance.
MODEL(S) 2COBB02F EGEA 200 HT UK 200 L HPWH HT series (UK market) 2COBB03F EGEA 260 HT UK 260 L HPWH HT series (UK market) 2COBB04F EGEA 200 LT UK 200 L HPWH LT series without solar coil (UK market) 2COBB05F EGEA 260 LT UK 260 L HPWH LT series without solar coil (UK market) 2COBB06F EGEA 200 LT-S UK 200 L HPWH LT series with solar coil (UK market) 2COBB07F EGEA 260 LT-S UK 260 L HPWH LT series with solar coil (UK market) 2CP0B22F EGEA TECH 200 HT UK 200 L HPWH HT series TECH version (UK market) 2CP0B23F EGEA TECH 260 HT UK 260 L HPWH HT series TECH version (UK market) 2CP0B24F EGEA TECH 200 LT UK 200 L HPWH LT series without solar coil TECH version (UK market) 2CP0B25F EGEA TECH 260 LT UK 260 L HPWH LT series without solar coil TECH version (UK market) 2CP0B26F EGEA TECH 200 LT-S UK 200 L HPWH LT series with solar coil TECH version (UK market) 2CP0B27F EGEA TECH 260 LT-S UK 260 L HPWH LT series with solar coil TECH version (UK market)
SIZE: See model.
SCOPE: Manufacturer recommended maximum working pressure 7 Bar & maximum operating temperature 90°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.
MARKING Ferroli, Model, Pressure and technical information on cylinder.
MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES No supply pipe or secondary circuit shall be permanently connected to a closed circuit for filling a heating system unless it incorporates an appropriate backflow prevention device. Expansion vessels should be installed in the vertical orientation, where expansion vessels are not installed in the vertical orientation appropriate measures should be used to ensure that there is adequate flow through of water through the expansion vessel and they are located so that the length of the connecting pipework is kept to a minimum. The discharge from the drain valve must be via a backflow protection device which gives fluid category 5 protection, for example a type AA or AB air gap or an air break to drain that complies with BS EN 1717.
ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.

Extra Notes